



TECHNICAL SPECIFICATION

MODELS	NITROGENEX	NITROGFILL	NITROPRO (N2 Generator)
Recommended Input Pressure (kg/cm²)	12	12	12
Purity of Nitrogen (%)	95-99	95-99	95-99
Storage Tank Size (Ltrs)	60	60	60
N ₂ Generating Capacity (lph)	3,500	3,500	3,500
Output Pressure (kg/cm²)	10	10	10
Pre set inflation	Yes	Yes	External input
Display	LCD	LCD	External input
Hose system (10 m)	Dual hose	Single hose	External input
Foot connector	Clip on	Clip on	External input
On time purity	Yes	NA	NA
Inflation mode	N2 / Air	N2 / Air	N2
Inflation system	In-Built	In-Built	External inflators*
Tyre pressure setting range	140 psi	170 psi	External input
Over all dimension (LxWxH) (mm)	502x540x1314	450x523x1311	450x523x1311

^{*}Wall Mount or Hand Held inflators

FEATURES & BENEFITS

- Automatic Nitrogen tyre inflating systems
- Generate Nitrogen by Pressure Swing Adsorption (PSA) technique
- Nitrogen / Air dual filling system
- Integrated storage tank for nitrogen gas
- · High grade filter separation unit

- Integrated vacuum system for removing air out of tyre before inflating with nitrogen*
- In-built digital counter*
- · On demand real time purity indicator*
- · Inlet & outlet pressure indicator

*Conditions apply



ADVANTAGE OF NITROGEN IN TYRES




- LONGER TYRE LIFE
- OXIDATION IS BLOCKED
- NITROGEN IS A GREEN ALTERNATIVE
- REDUCES THE TYRE'S RUNNING TEMPERATURE
- IMPROVES THE RIDE QUALITY
- INCREASES TYRE LIFE
- KEEPS TYRE PRESSURES MORE CONSTANT
- SLOWS THE RATE OF PRESSURE LOSS
- DOESN'T REACT WITH THE TYRE AND RIM MATERIALS

OUR STRENGTH



OUR NETWORK



ATS ELGI

Private Industrial Estate, Kurichy, Coimbatore - 641021, Tamil Nadu, India.

Tel: +91-422-2589999 | Email: enquiry@ats-elgi.com

Visit us at : www.ats-elgi.com

Toll Free Number: 1800-203-3544 / 1800-405-3544

ATS ELGI authorized dealer